



Features ActivePure Technology proven to reduce viruses, bacteria, and other pathogens (full list of tested pathogens available below in “The Proof”)

THE TECHNOLOGY

The Vollara Air & Surface Pro+ combines multiple complementary technologies, including HEPA, activated carbon, ozone, and ActivePure® Technology. Patented ActivePure Technology is the most powerful surface and air purification ever discovered. It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in “The Proof” section below).

ActivePure does not replace the need to follow CDC guidance and should be used as a complementary technology.

THE PROOF

In extensive independent lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens:

- SARS-CoV-2 – RNA Virus
- H1N1 Influenza
- H5N8 Influenza
- Murine Norovirus
- PhiX-174
- MS2 Bacteriophage
- MRSA
- E. coli
- Salmonella enterica
- Legionella pneumophila
- Clostridium difficile
- Bacillus globigii
- Erwinia herbicola
- Listeria monocytogenes
- Candida auris
- Botrytis cinerea
- Sclerotinia sclerotiorum
- Aspergillus versicolor
- Aspergillus niger endospores
- Methicillin-resistant Staphylococcus epidermis
- Staphylococcus epidermidis

THE BENEFITS

The Vollara Air & Surface Pro+ provides continuous surface decontamination and air purification in real time without the use of harmful chemicals. It is an automated, proactive, and effective solution for your home or business.

- Portable, lightweight device
- No installation - plug-and-play solution
- Easy to use and low maintenance
- Proven effective against many common viruses, bacteria, molds, and fungi
- Reduces smoke, allergens, odors, and VOCs



SPECIFICATIONS

Product Information	9940063 Model : A1041B *NOTE: This product does not meet California requirements and cannot be shipped to California or Canada.
Technology Included	ActivePure® Cell Positive & Negative Multi-point and RF Ionizers Purification Plate HEPA & Activated Carbon Filter
Electrical	Input Voltage: 100 ~ 240 VAC; 50/60 Hz external power supply; DC 24 Volts; 1.5 Amps Max Power Consumption: 43 Watts Max. Conforms to UL STD 867. Certified to CSA STD C22.2 250-08
Mechanical	Nominal Airflow Rate: 40-60 CFM Adjustable Fan Speed
Weight & Dimensions	7.6 lbs (3.5 kg) 11.75" H x 9.5" W x 10" D (29.8 cm x 24.1 cm x 25.4 cm)
Operating Temperature	34°F – 100°F (-1°C – 38°C)
Noise Level	45 dB(A) (on low); 55 dB(A) (on high)
Recommended Maximum Coverage in a Contiguous Space ¹	Up to 2,000 sq. ft. (185m ²) depending on occupant density and other factors. High density commercial not to exceed 500 sq. ft. (46m ²). For coverage in medical or health care environments, contact Medical@activepure.com .
Warranty	Limited 3 year warranty



Contact Name: _____



Email: _____



Phone Number: _____

1. Assumes 8 foot ceilings. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, other layers of protection, and worst case desired outcomes